



ULS620

Features

- Ultra low phase noise $\leq -88\text{dBc/Hz}@10\text{Hz}$, $\leq -154\text{dBc/Hz}@10\text{kHz}$, $\leq -172\text{dBc/Hz}@1\text{MHz}$ (1GHz)

Applications


- Frequency standards and sources
- Measuring and calibration equipment

Technical Specifications

Standard Frequency	100MHz	1GHz	100MHz	1GHz	100MHz	1GHz	100MHz	1GHz
Phase Noise (dBc/Hz,free-running)	Option: S		Option: H		Option: L		Option: U	
10 Hz	-100	-80	-103	-83	-105	-85	-108	-88
100 Hz	-130	-110	-133	-113	-135	-115	-138	-118
1 KHz	-160	-140	-163	-143	-165	-145	-168	-148
10 KHz	-171	-149	-172	-150	-173	-152	-175	-154
100 KHz	-173	-152	-173	-155	-175	-157	-175	-160
1 MHz	-174	-165	-174	-168	-176	-170	-176	-172
Aging (after 30 days of continuous operation)	$\leq 5 \times 10^{-7}$ / year							
Input voltage range	12 VDC \pm 5%							
Power consumption (at 25°C)	8W / 5W							
Warm up time (at 25°C to 2×10^{-7})	≤ 5 min							
Input EFC								
Tuning range	$\geq \pm 5 \times 10^{-7}$ (0 ~ 10 V, Positive)							
Output specifications								
Wave form	Sine wave							
Number of outputs	4							
Port to port isolation (Same frequency)	≥ 30 dB							
Power	10 ± 3 dBm							
Harmonics	≤ -30 dBc							
Spurious	≤ -100 dBc							
Frequency stability vs Temperature (-40°C to 70°C)	$\leq 2 \times 10^{-7}$							
Load	$50 \Omega \pm 5\%$							
g sensitivity	$\leq 5 \times 10^{-10}$ / g							
Vibration	MIL-STD-202G							
Size (L×W×H)	110×70×24mm ³							



Outline drawing and Electrical connections (mm)



- OUT1: 100MHz (SMA-F)
- OUT2: 100MHz (SMA-F)
- OUT3: 1GHz (SMA-F)
- OUT4: 1GHz (SMA-F)
- +12V: +12V Power supply
- C : EFC

